

Редукция Давления / Pressure Reducing / Reductoras de Presión / Réduction de Pression

Код	Ø		Евро
	мм	Дюйм	
PN16 HMARP2M16050F	50	2"	
HMARP2M16065F	65	2½"	
HMARP2M16080F	80	3"	
HMARP2M16100F	100	4"	
HMARP2M16125F	125	5"	
HMARP2M16150F	150	6"	
HMARP2M16200F	200	8"	
HMARP2M16250F	250	10"	
HMARP2M16300F	300	12"	
HMARP2M16350F	350	14"	
HMARP2M16400F	400	16"	
Ø 400-500-600 (16"-20"-24")			
Ø 700-800 (28"-32")			



Код	Ø		Евро
	мм	Дюйм	
PN25 HMARP2M25050F	50	2"	
HMARP2M25065F	65	2½"	
HMARP2M25080F	80	3"	
HMARP2M25100F	100	4"	
HMARP2M25125F	125	5"	
HMARP2M25150F	150	6"	
HMARP2M25200F	200	8"	
HMARP2M25250F	250	10"	
HMARP2M25300F	300	12"	
HMARP2M25350F	350	14"	
HMARP2M25400F	400	16"	
Ø 400-500-600 (16"-20"-24")			
Ø 700-800 (28"-32")			



HM-RP2M

Стандарт 0,5 ÷ 7,0 bar
PN16
2-way

Дополнительно 1,0 ÷ 13,0 bar
PN25



Дополнительные функции / Additional Functions / Funciones Adicionales / Fonctions Supplémentaires



HM-RP2M + **EL2** 2-х ходовой Соленоид / 2-way solenoid / Solenoide de 2 vías / Solenoide 2 voies (24V AC PN16)

Евро

Поддержка Давления / Pressure Sustaining / Sostenedoras de Presión / Mainteneur de Pression

Код	Ø		Евро
	мм	Дюйм	
PN16 HMASP2M16050F	50	2"	
HMASP2M16065F	65	2½"	
HMASP2M16080F	80	3"	
HMASP2M16100F	100	4"	
HMASP2M16125F	125	5"	
HMASP2M16150F	150	6"	
HMASP2M16200F	200	8"	
HMASP2M16250F	250	10"	
HMASP2M16300F	300	12"	
HMASP2M16350F	350	14"	
HMASP2M16400F	400	16"	
Ø 400-500-600 (16"-20"-24")			
Ø 700-800 (28"-32")			



Код	Ø		Евро
	мм	Дюйм	
PN25 HMASP2M25050F	50	2"	
HMASP2M25065F	65	2½"	
HMASP2M25080F	80	3"	
HMASP2M25100F	100	4"	
HMASP2M25125F	125	5"	
HMASP2M25150F	150	6"	
HMASP2M25200F	200	8"	
HMASP2M25250F	250	10"	
HMASP2M25300F	300	12"	
HMASP2M25350F	350	14"	
HMASP2M25400F	400	16"	
Ø 400-500-600 (16"-20"-24")			
Ø 700-800 (28"-32")			



HM-SP2M

Стандарт 0,5 ÷ 7,0 bar
PN25
2-way

Дополнительно 1,0 ÷ 13,0 bar



Дополнительные функции / Additional Functions / Funciones Adicionales / Fonctions Supplémentaires



HM-SP2M + **EL2** 2-х ходовой Соленоид / 2-way solenoid / Solenoide de 2 vías / Solenoide 2 voies (24V AC PN16)

Евро

Регулирование Расхода / Flow Rate Control / Reguladora de Caudal / Contrôle de Débit

Код	Ø		Евро
	мм	Дюйм	
PN16 HMAQP2M16050F	50	2"	
HMAQP2M16065F	65	2½"	
HMAQP2M16080F	80	3"	
HMAQP2M16100F	100	4"	
HMAQP2M16125F	125	5"	
HMAQP2M16150F	150	6"	
HMAQP2M16200F	200	8"	
HMAQP2M16250F	250	10"	
HMAQP2M16300F	300	12"	
HMAQP2M16350F	350	14"	
HMAQP2M16400F	400	16"	
Ø 400-500-600 (16"-20"-24")			
Ø 700-800 (28"-32")			



Код	Ø		Евро
	мм	Дюйм	
PN25 HMAQP2M25050F	50	2"	
HMAQP2M25065F	65	2½"	
HMAQP2M25080F	80	3"	
HMAQP2M25100F	100	4"	
HMAQP2M25125F	125	5"	
HMAQP2M25150F	150	6"	
HMAQP2M25200F	200	8"	
HMAQP2M25250F	250	10"	
HMAQP2M25300F	300	12"	
HMAQP2M25350F	350	14"	
HMAQP2M25400F	400	16"	
Ø 400-500-600 (16"-20"-24")			
Ø 700-800 (28"-32")			



HM-QP2M

Стандарт PN16

Дополнительно



Дополнительные функции / Additional Functions / Funciones Adicionales / Fonctions Supplémentaires



HM-QP2M + **RP2M** Pilota riduttore / Pressure reducing pilot / Piloto reductor / Pilote réducteur

Евро